## TFE

## **MULCHER**

- 1 Body built in high strength steel.
- 2 Double chain curtains for front protection.
- 3 Hydraulic hood to improve the material entrance.
- 4 Sidestep system on body sides.
- 5 Fixed bolted head.
- 6 Bolted fixed skids.
- 7 Rotor with replaceable shafts, with fixed hammers with helical disposition and with "P-CUT" depth bite limiters.
- 8 Transmission with 4 XPB belts.
- 9 Gearbox with built-in free-wheel, input to 540 rpm and 1 3/8" Z6.
- 10 Reinforced PTO shaft.
- 11 TMC Cancela F49 reversible hammers.
- **12** Replaceable counterblades C01 + adjustable entrance counterblade.
- 13 PTO shaft included with 1 3/8" Z6 tractor side.







MOD.				TFE-125	TFE-150	TFE-180
TECHNICAL FEA	TURES					
Working width (m)			1,25	1,50	1,80	
Total width (m)			1,54	1,79	2,09	
Required input power (HP)			40	50	60	
Max. allowed power (HP)			70			
Rotor/s cutting diameter (mm)			325			
Gearbox input speed (rpm)			540			
Nr. of hammers F49 + F38 / F09 + F38 / F08 + F38		30 + 2	36 + 2	44 + 2		
Counterblades			4 replaceable rows			
Coupling category			Cat. 1 / Cat. 2			
Nr. of belts - type			4 XPB			
Skids			Fixed bolted (1 position)			
Weight (kg)			625	685	755	
REF. MOD.			НМ0Н01	HM0H15	HM0H18	
OPTIONS						
401	Rotor mounted with hammers F09					
340	Rotor mounted with hammers F08					
050	Mechanical rear pushing frame					
242	Rubber protection at front					
KM1.F49.0H	Maintenance basic kit (2 hammers F49 + 2 bolts + grease)					
KM2.F49.0H	Maintenance kit (basic kit + 4 belts XPB)					
KM1.F08.0H	Maintenance basic kit (2 hammers F08 + 2 bolts + grease)					
KM2.F08.0H	Maintenance kit (basic kit + 4 belts XPB)					
KM1.F09.0H	Maintenance basic kit (2 hammers F09 + 2 bolts + grease)					
KM2.F09.0H	Maintenance kit (basic kit + 4 belts XPB)					
OTHERS						
DTO shoft value (treates side)		T1	T2	Т3		T4
PIU snatt yol	PTO shaft yoke (tractor side)		1 3/8" Z21	1 3/4"	Z6 .	3/4" Z20





Hammer F08 Optional

Hammer F38 Standard (sides)

Counterblade C01 Standard









