

TFT

MULCHER

- 1 Body built in high strength steel with special design in the front to improve the material entrance.
- 2 4 chain curtains for front protection + 4 extra chain curtains in the middle.
- 3 Coupling to tractor Cat. 3 with fast coupling balls.
- 4 3rd hydraulic point with permanent aligning device (patented). Yoke tractor side Ø32 mm.
- 5 Hydraulic hood with "Superfinish" system.
- 6 Sidestep system on body sides.
- 7 Skids with 2 height positions and side protection.
- 8 Rotor with replaceable shafts, with fixed hammers with helical disposition.
- 9 Hammers with carbide tips and different configurations.
- 10 Transmission with 12 XPC belts, ESB system and automatic belt tensioner.
- 11 Gearbox with built-in free-wheel, input to 1.000 rpm and 1 3/4" Z20.
- 12 Reinforced PTO shaft.
- 13 Replaceable counterblades on body frame and on hydraulic hood.
- 14 Hammers with 2 carbide tips TMC Cancela F19 + F20 (standard).
- 15 PTO shaft included with 1 3/4" Z20 tractor side.



MOD.		TFT-225	TFT-250			
TECHNICAL FEATURES						
Working width [m]		2,25	2,50			
Total width [m]		2,85	3,05			
Required input power [HP]		280	300			
Max. allowed power [HP]		390				
Rotor/s cutting diameter (mm)		632,5				
Gearbox input speed (rpm)		1.000				
Nr. of hammers	F19 + F20 / F25 + F20	54 + 2	58 + 2			
	F05 + F13	40 + 2	46 + 2			
	F23	56	60			
Counterblades		1 fixed row + 4 replaceable rows				
Coupling category		Cat. 3				
Nr. of belts - type		12 XPC				
Skids		Adjustable bolted (2 positions)				
Weight [kg]		3.635	3.785			
REF. MOD.		HMOX03	HMOX25			
OPTIONS						
345	Rotor mounted with hammers F25					
316	Rotor mounted with hammers F23					
291	Rotor mounted with hammers F05 + F13					
123	Hydraulic rear pushing frame with raker teeth					
366	Reinforced hydraulic rear pushing frame with raker teeth					
055	Kit turbo PREMIUM					
323	Kit turbo					
057	Skids to work a little bit deeper*					
335	Automatic greasing kit					
KM1.F05.0X	Maintenance basic kit (2 hammers F05 + 4 bolts + grease)					
KM2.F05.0X	Maintenance kit (basic kit + 12 belts XPC)					
KM1.F19.0X	Maintenance basic kit (2 hammers F19 + 2 bolts + 2 nuts + grease)					
KM2.F19.0X	Maintenance kit (basic kit + 12 belts XPC)					
KM1.F25.0X	Maintenance basic kit (2 hammers F25 + 2 bolts + 2 nuts + grease)					
KM2.F25.0X	Maintenance kit (basic kit + 12 belts XPC)					
KM1.F23.0X	Maintenance basic kit (2 hammers F23 + 2 bolts + 2 nuts + grease)					
KM2.F23.0X	Maintenance kit (basic kit + 12 belts XPC)					
OTHERS						
PTO shaft yoke (tractor side)		T1	T2	T3	T4	T5
		1 3/8" Z6	1 3/8" Z21	1 3/4" Z6	1 3/4" Z20	D8x32x38
3rd point alignment device yoke type (tractor side)	H1	H2	H3	H4	H5	H6
	Ø25	Ø28	Ø32	Ø36	Ø40	Ø45

* This option excludes the Turbo Kit

