

TXX

MULCHER

- 1 Body built in high strength steel.
- 2 Protection at front by a quadruple curtain of chains.
- 3 Hydraulic cover with a screen at rear to classify the material and with a built-in leveler.
- 4 Body sides with Sidestep system.
- 5 Adjustable in height skids with 3 positions and with deflectors to help the material to enter into the chamber.
- 6 Rotor with fixed hammers with helical disposition.
- 7 Internal modular replaceable shell in wear resistant steel.
- 8 Adjustable input counterblade.
- 9 Transmission with 6 + 6 XPB belts and automatic tensioners.
- 10 Gearbox with built-in free-wheel, input to 1.000 rpm and 1 3/4" Z6.
- 11 Hammers with 2 carbide tips model F29.
- 12 PTO shaft included with 1 3/8 Z6" tractor side.



HARDOX
IN MY BODY

FLEXI
STEEL



MOD.		TXX-200	TXX-225	TXX-250		
TECHNICAL FEATURES						
Working width (m)		2,00	2,25	2,50		
Total width (m)		2,51	2,76	3,01		
Required input power (HP)		140	150	170		
Max. allowed power (HP)		300				
Rotor/s cutting diameter (mm)		519				
Gearbox input speed (rpm)		1.000				
Nr. of hammers	F29	34	38	42		
Counterblades		1 adjustable				
Coupling category		Cat. 3				
Nr. of belts - type		12 XPB (automatic tensioner)				
Skids		HARDOX (3 positions)				
Adjustable height control		Skids				
Weight (kg)		2.490	2.680	2.780		
REF. MOD.		HM7Q20	HM7Q03	HM7Q25		
OPTIONS						
335	Automatic greasing kit					
058	Rear roller for compacting the soil					
376	Rear leveler with hydraulic adjustment					
KM1.F29.7Q	Maintenance basic kit (2 hammers F29 + 2 bolts + 2 nuts + grease)					
KM2.F29.7Q	Maintenance kit (basic kit + 12 belts XPB)					
OTHERS						
PTO shaft yoke (tractor side)		T1	T2	T3	T4	T5
		1 3/8" Z6	1 3/8" Z21	1 3/4" Z6	1 3/4" Z20	D8x32x38

Hammer F29 Standard

