



TMC  CANCELA®

www.tmccancela.com
info@tmccancela.com



MULTIPURPOSE

TMC  CANCELA®
Javier Cancela



MPS
MPK
MFX
FORESTRY



QUALITY AND COMMITMENT ON WHAT WE DO

THE WAY WE WORK REMAINS FAITHFUL TO THE ORIGINS OF TMC CANCELA.
Our main target is to provide the best equipment and guarantee the excellence of our products. Immersed in a constant learning, we incorporate the latest technological innovations to our processes, achieving robust and efficient machinery adapted to the needs of the market.

tmccancela.com



Hydraulic hood with "Superfinish" system.



Replaceable protection skids for deep work.

MFX

Ø 18 in/450 mm
MAXIMUM DIAMETER TO
MULCH
300-400
HP [min-max]



Reinforced gearbox, input to 1,000 rpm and 1 3/4" Z20, with cooling system.

MPS

Ø 14 in/350 mm
MAXIMUM DIAMETER TO
MULCH
140-180
HP [min-max]

Hammers with 2 carbide tips TMC Cancela model F19 + F20 (Standard).

Hammer F19
Hammer F20 (sides)

MPK

Ø 18 in/450 mm
MAXIMUM DIAMETER TO
MULCH
220-280
HP [min-max]

Replaceable protection skids for deep work.

Two-speed output reinforced gearbox (manual shift), input to 1,000 rpm and 1 3/4" Z20, with cooling system.

TECHNICAL FEATURES

MOD.	MPS-225	MPK-250	MFX-250
Working width (in/m)	89 / 2.25	98 / 2.50	98 / 2.50
Total width (in/m)	104 / 2.65	126 / 3.20	118 / 2.99
Required input power (HP)	140	220	300
Max. allowed power (HP)	180	280	400
Rotor/s cutting diameter (in/mm)	19 / 475	25 / 632.5	31 / 790
Gearbox input speed (rpm)	540 / 1,000	1,000	1,000
Nr. of hammers	F19 + F20 / F25 + F20 / F45 + F20 F23 F21 + F42 + F37	- - 58 + 2 + 2	- - 58 + 2 + 2
Counterblades	4 replaceable rows HDX	6 HDX replaceable rows	5 HDX replaceable rows + 1 adjustable counterblade
Coupling category	Cat. 2	Cat. 3	Cat. 3
Nr. of belts - type	12 XPB	12 XPC	2 side cascade gearboxes
Skids	Replaceable bolted	Replaceable bolted	Replaceable bolted
Weight (lbs/kg)	5,110 / 2,318	8,962 / 4,065	12,456 / 5,650

3rd hydraulic point with permanent aligning device (patented). Yoke tractor side Ø32 mm/1.26 in.



Coupling to tractor Cat. 3 with fast coupling balls.

Protection by four chain curtains.



Replaceable protection skids for deep work.

Two-speed output reinforced gearbox (manual shift), input to 1,000 rpm and 1 3/4" Z20, with cooling system.

3rd hydraulic point with permanent aligning device (patented). Yoke tractor side Ø32 mm/1.26 in.



Sidestep system on body sides.

Protection by four chain curtains.

TMC Cancela F21 + F42 + F37 hammers with single tugsten carbide tips.

Hammer F21
Hammer F42 (sides)
Hammer F37 (sides)

