



TMC  CANCELA®

[www.tmccancela.com](http://www.tmccancela.com)  
[info@tmccancela.com](mailto:info@tmccancela.com)



LIGHT-MEDIUM RANGE

TMC  CANCELA®  
*Javier Cancela*



TFE  
TFJ  
TFS  
TFK +  
TFX  
FORESTRY



### QUALITY AND COMMITMENT ON WHAT WE DO

THE WAY WE WORK REMAINS FAITHFUL TO THE ORIGINS OF TMC CANCELA.  
Our main target is to provide the best equipment and guarantee the excellence of our products. Immersed in a constant learning, we incorporate the latest technological innovations to our processes, achieving robust and efficient machinery adapted to the needs of the market.

[tmccancela.com](http://tmccancela.com)



# TECHNICAL FEATURES

MOD.	TFE-150	TFJ-150D	TFJ-180D	TFS-180	TFS-200	TFK-225+	TFX-225
Working width (in/m)	59 / 1.50	59 / 1.50	71 / 1.80	71 / 1.80	79 / 2.00	89 / 2.25	89 / 2.25
Total width (in/m)	70 / 1.79	70 / 1.79	82 / 2.09	86 / 2.18	94 / 2.38	107 / 2.72	108 / 2.74
Required input power (HP)	50	50	60	80	95	145	160
Max. allowed power (HP)	70	90		110		200	250
Rotor/s cutting diameter (in/mm)	13 / 325	15 / 375		16 / 413		18 / 455	20 / 508
Gearbox input speed (rpm)	540	540		540		1,000	1,000
Nr. of hammers	F49 + F39 / F09 + F39 / F08 + F38 F19 + F20 / F25 + F20 / F45 + F20	36 + 2	44 + 2	42 + 2	46 + 2	54 + 2	54 + 2
Counterblades	4 replaceable rows	4 replaceable rows		1 fixed row + 3 replaceable rows		1 fixed row (replaceable counter chassis) + 3 replaceable rows	1 fixed row + 3 replaceable rows
Coupling category	Cat. 1 / Cat. 2	Cat. 2N / Cat. 2		Cat. 2		Cat. 3N	Cat. 3N
Nr. of belts - type	4 XPB	4 XPB		6 XPB		10 XPB	12 XPB
Skids	Fixed bolted (1 position)	Adjustable bolted (2 positions)		Adjustable bolted (2 positions)		Adjustable bolted (2 positions)	Adjustable bolted (2 positions)
Weight (lbs/kg)	1,510 / 685	1,885 / 855	2,083 / 945	2,831 / 1.284	2,978 / 1.351	4,696 / 2.130	5,007 / 2.271
Hydraulic cylinder stroke (in/mm)	-	16 / 400		-		-	-

