



TMC  CANCELA®

[www.tmccancela.com](http://www.tmccancela.com)  
[info@tmccancela.com](mailto:info@tmccancela.com)



SPECIAL FOR PRUNNING RESTS

TMC  CANCELA®  
*Javier Cancela*



TPS  
TVS-R  
TOS-R  
TOA  
AGRICULTURAL



**QUALITY AND COMMITMENT  
ON WHAT WE DO**

THE WAY WE WORK REMAINS FAITHFUL TO THE ORIGINS OF TMC CANCELA.

Our main target is to provide the best equipment and guarantee the excellence of our products. Immersed in a constant learning, we incorporate the latest technological innovations to our processes, achieving robust and efficient machinery adapted to the needs of the market.

[tmccancela.com](http://tmccancela.com)



# TECHNICAL FEATURES

MOD.	TPS-180D	TPS-200D	TPS-220D	TVS-R-150	TVS-R-180	TVS-R-200	TOS-R-180	TOS-R-210	TOA-210	TOA-240	TOA-300	
Working width (in/m)	71 / 1.80	79 / 2.00	86 / 2.20	59 / 1.50	71 / 1.80	79 / 2.00	71 / 1.80	83 / 2.10	83 / 2.10	94 / 2.40	118 / 3.00	
Total width (in/m)	80 / 2.02	87 / 2.22	95 / 2.42	67 / 1.71	79 / 2.01	87 / 2.21	89 / 2.25	101 / 2.56	98 / 2.50	110 / 2.80	134 / 3.40	
Required input power (HP)	65	70	75	80	90	100	130	150	100	100	100	
Max. allowed power (HP)	90			100			200		200			
Rotor/s cutting diameter (in/mm)	15.1 / 385			16 / 405			21 / 539		21 / 545			
Gearbox input speed (rpm)	540			540 (1,000 as option)			500 (1,000 as option)		540 (1,000 as option)			
Nr. of hammers	A06			20 + 20	22 + 22	26 + 26	22 + 22	22 + 22	26 + 26	30 + 30	38 + 38	
	A01	28	32	34								
	A03	84	96	102								
Nr. of knives												
Counterblades	2 replaceable rows			2 replaceable rows + 1 fixed row			2 replaceable rows + 1 fixed row		3 replaceable rows + 1 fixed row			
Coupling category	Cat. 1 / Cat. 2			-			-		-			
Skids	Fixed bolted (1 position)			-			-		-			
Nr. of belts - type	4 XPB			4 XPB			6 XPB		6 XPB			
Adjustable height control	Rear roller			Wheels / Drawbar			Wheels / Drawbar		Wheels / Drawbar			
Weight (lbs / kg)	1,312 / 595	1,444 / 655	1,554 / 705	2,822 / 1,280	3,250 / 1,475	3,505 / 1,590	3,790 / 1,720	4,520 / 2,050	5,425 / 2,460	6,060 / 2,750	7,100 / 3,220	
Hydraulic cylinder stroke (in/mm)	16 / 400											
Working reach	mechanical	34-52 /	34-64 /	37-72 /	30-30 /	36-36 /	40-40 /	36-36 /	42-42 /	42-42 /	48-48 /	60-60 /
	(in/mm)	869.5-1,330.5	869.5-1,632.5	948.5-1,832.5	768-768	918-918	1,017-1,017	918-918	1,068-1,068	1,068-1,068	1,218-1,218	1,518-1,518

